

Amendments to the Specification:

In the Abstract, please replace the paragraph in its entirety with:

A pull pin assembly includes: a first pole having a first hole; a second pole having a second hole, and sliding in the first pole; a main body having a central hollow containing the first pole; a pull pin body extending radially from the central hollow, and having a space extending into the central hollow; a pull pin, having a circumferential stop, disposed in the space to move from a first position extending into the central hollow through the first hole to a second position outside the central hollow; a pull pin plug fit into the space and having a hollow containing the pull pin; and a biasing member biasing the pull pin toward the [second] first position to lock the first and second poles; wherein the biasing member is disposed to bias the pull pin between the circumferential stop and the pull pin plug.

In column 1, lines 37 - 57, please replace the paragraph in its entirety with:

In accordance with the present invention there is provided a pull pin assembly comprising: a first rod or pole, having a first hole and a second notch or hole, and a second rod or pole, having third hole, the second rod or pole being slidably contained within the first rod or pole, so that the first hole is superimposable on the second hole. A main body is provided having a central hollow dimensioned to contain the first rod or pole, and having at least one resilient tab, the resilient tab being cut out from the main body and having a boss thereon

extending into the central hollow to engage the second notch or hole of the first rod or pole. A pull pin body is provided integral with the main body and extending radially outward from the central hollow, the pin body having a space therein extending into the central hollow. A pull pin is slidably disposed in the space of the pull pin body to move from a first position extending into the central hollow through the first hole to a second position outside of the central hollow. A biasing member biases the pull pin toward the [second] first position to relatively lock the first rod or pole and the second rod or pole when the first hole is superimposed on the second hole.

In column 2, lines 16 - 20, please replace the paragraph in its entirety with:

The central hollow, first rod or pole and second rod or pole all preferably have square cross sections. The main body preferably further comprises a lip disposed to engage [and] an end of said first rod or pole. The pull pin plug is preferably countersunk and friction fit into the pull pin body.

In column 2, lines 21 - 49, please replace the paragraph in its entirety with:

In a still further embodiment, the present invention provides a pull pin assembly, comprising: a rod or pole, having a hole; and a main body, having a central hollow dimensioned to contain the rod or pole. A pull pin body is preferably provided integral with the main body and extending radially outward from the central hollow, the pin body having a space therein extending into the central hollow. A pull pin is slidably disposed in the

space of the pull pin body to move from a first position extending into the central hollow through the first hole to a second position outside of the central hollow, the pull pin having a circumferential stop. A pull pin plug is fit into the space of the pin body, the pull pin plug having a hollow dimensioned to slidably contain the pull pin. A biasing member is provided biasing the pull pin toward the [second] first position to relatively lock the first rod or pole and the second rod or pole when the first hole is superimposed on the second hole. In this [embedment] embodiment, the biasing member is disposed to bias the pull pin between the circumferential stop and the pull pin plug, and wherein the circumferential stop is dimensioned to prevent the pull pin from passing completely through the first hole in the second position. Preferably, the pull pin comprises a circumferential tongue, wherein the pull pin plug comprises a radial groove, wherein, the pull pin has a first engageable position in which the circumferential tongue is movable in the radial groove, and a second, disengaged position, wherein the pull pin is radially pulled against a biasing force of the biasing member to come out of the radial groove and rotated so that the circumferential tongue is biased against the pull pin plug.

In column 2, lines 61 - 66, please replace the paragraph in its entirety with:

FIG. 3 is a cross section of the pull pin assembly of one embodiment of the present invention.

FIG. 4 is a further cross section of the pull pin assembly of the [present invention] embodiment shown in FIG. 3.

FIG. 5 is [yet another] a cross section of the pull pin assembly of FIG. 4 [of the present invention] taken [alone] along the line I-I [in FIG. 4].

In column 3, lines 1 - 2, please replace the paragraph in its entirety with:

FIG. 6 is a top view cross section of the pull pin assembly of [the present invention] FIG. 3.

In column 3, lines 10 - 25, please replace the paragraph in its entirety with:

FIG. 2 shows a preferred embodiment of the pull pin assembly 20 of the present invention. Main body 21 is fit over an end of pole 12 of an upright 8 of portable canopy 10 (as shown in FIG. 1). As shown in FIGS. 2 and 6, [A] a resilient tab 26 is cut out from main body 21 by slots 28, and a boss 27 on tab 26 engages a hole 60 to fix the main body 21 to the assembly 20. In this manner, the main body can be easily fixed to pole 12 without the necessity of special tools or adhesives. While the body 21 is also preferably friction fit to pole 12, tab 26 and boss 27 ensure that the main body 21 is securely fit to pole 12, without the necessity for precise tolerances. While only one tab 26 is visible in FIG. 2, the preferred embodiment has a corresponding, symmetrically-arranged second tab 26 on a side of pole [11] 12 not seen in the FIG. 2. A second boss 27 fit into second hole 60 is shown in FIG. 6. The number, size, and dimensions of resilient tabs 26 can be varied, however.

In column 3, lines 26 - 37, please replace the paragraph in its entirety with:

Preliminary Amendment for Reissue Application

Amendment Date March 29, 2004

Original Patent No. 6,575,656 B2

A pull pin body 22, integral with main body 21 extends radially outward from main body 21. A pull pin 24 is slidably contained in the pull pin body 22. At a distal end of pull pin 24 is a pull ring 25 fitted through a transverse hole 34 (shown in FIG.3) at the distal end of pin 24. As shown in FIG 3 and as will be discussed further below, pulling pull pin 24 from a first position in which the pin extends through two superimposed holes 36, 37 into a central hollow 62 of the assembly to a second position outside of the hollow, releases pole 11 from pole 12 so as to allow relative movement of poles 11, 12 in the direction of the double headed arrow of FIG. 3. In the present embodiment, poles 11 and 12 have a square cross section.

In column 3, lines 38 - 57, please replace the paragraph in its entirety with:

FIG. 3 shows a cross section of the assembly according to one embodiment of the present invention. In FIG. 3, pull pin 24 is shown in the second position , outside of central hollow 62. As discussed above, pull pin 24 is slidably contained inside pull pin body 22 within a space 30 and a hole 51 in plug 23. Plug 23 is countersunk and preferably friction fit into pull pin body 22 (shown in FIG. 5) to maintain its position. A spring 32 serves as a biasing member to bias the pull pin 24 toward the first position in which the pull pin 24 extends into the central space 62. Spring 32 acts between an inner surface 39 of plug 23 and a circumferential stop 31 of pull pin 24. A hole 35 is provided at the end of space 30 closest to the central hollow 62. The hole 35 is surrounded by a circumferential ledge 38 having a circumference substantially the same as space 30. In FIG. 3, hole 35 is superimposed on likewise superimposed holes 36 and 37 of poles 12 and 11, respectively. Also shown in FIG. 3, is lip

Preliminary Amendment for Reissue Application

Amendment Date March 29, 2004

Original Patent No. 6,575,656 B2

40 of main body 21. Lip 40 serves not only to protect the end of pole 12 from damage, but also to guide pole 11 as it slides in and out of pole 12 in a telescopic manner to extend and collapse upright 8.

In column 3, lines 58 - 64, please replace the paragraph in its entirety with:

FIG. 4 shows a cross section identical to the embodiment shown in FIG. 3, except that pull pin 24 is in the first position, extending through holes 35, 36, 37 into central hollow 62, thus locking poles 11 and 12 together. FIG. 4 also shows that circumferential stop 31 also serves to prevent more than a predetermined length of pull pin 24 from extending past hole 35, by abutting against circumferential ledge 38.

In column 3, line 65 through column 4, line 21, please replace the paragraph in its entirety with:

FIG. 5 shows a cross section along line I-I in FIG. 4. As shown in FIG. 5, a tongue 33 is provided on the outer circumference of pull pin 24. Tongue 33 slides within a groove 50 provided in hole 51 of plug 23. As shown in FIG. 2, when the pull pin 24 is moved from the first position to the second position, tongue 33 comes out of groove 50 allowing pull pin 24 to be rotated from position A to position B (as shown in FIG. 2). In position B, the groove is biased toward an outer surface of plug 23 and the pin is held by friction in the second position. In this locked, second position, the poles 11 and 12 are, of course, free to move relative to one another and the upright 8 can be extended or collapsed, as desired. Pull pin 24 is moved from position B to position A by pulling pull pin 24, by means of pull ring 25,

Preliminary Amendment for Reissue Application

Amendment Date March 29, 2004

Original Patent No. 6,575,656 B2

slightly outward against the biasing force of spring 32, rotating pull pin 24 by means of ring 25, positioning tongue 33 at an entrance to groove 50 and releasing pull ring 25 so that pull pin 24 once again moves toward the first position by the biasing force of spring 33. Also shown in FIG. 2 are several holes 37, each of which can be superimposed on holes 35 and 36, so that, when the pull pin is moved back through holes 35, 36, 37 to the first position, poles 11 and 12 are once again relatively locked together as shown, for example, in FIG. 4.